

PRIMER WB

Water-based one-component acrylic primer for cementitious surfaces.

DESCRIPTION

PRIMER WB is an acrylic monocomponent based on non-yellowing water-based resins designed for the preparation of cement surfaces prior to treatment with IDEAL PU WB-EASY resins.

PRIMER WB's lasting surface film is bonded to clean and healthy cement surfaces. Used in combination with PUWB-EASY creates an anti-yellowing membrane and guarantees excellent resistance to penetration of contaminants and abrasion.

FIELDS OF APPLICATION

- Microtopping floorings and coatings
- Acidified and Cloudy Floors
- Flooring in Architop

TECHNICAL SPECIFICATIONS

Typical properties:

Rate of Consumption: 40 g / m²

Overlapping with PUWB_EASY (without mapping) 3-4 h (*)

Application temperature + 10 ° to + 25 °

(*) at 20 ° and 65% UR

APPLICATION

For maximum results:

- PRIMER WB should be applied in a thin, uniformed layer. It is recommended to provide good air circulation to improve the drying phase and film properties.
- PRIMER WB drying takes place by evaporation of water. For proper film development, apply only when the surface temperature is above 10 ° C and the relative humidity (air) is below 80%.
- For application wait at least 4 days on Microtopping, at least 2 days on Architop, over nuvolati in cls wait for full maturation.
- DO NOT REMOVE. Do not store at temperatures below 5 ° C.

Cleaning the tools: before the resin is dry, clean with water.

Rate of consumption of 40 g / m².

PACKAGING AND STORAGE

PRIMER WB is supplied in tanks from Lt 5.

PRIMER WB keeps for at least twelve months in the sealed original container.

NOTICE

Avoid skin and eye contact; product is harmful if swallowed. For use in closed areas provide appropriate ventilation. Product residues and empty containers are to be disposed of in compliance with local regulations.

IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organizes periodical training of its customers on demand. Anyone who uses these products without qualification does so at their own risk.

- PRIMER WB EDIZ. 01 of 11/10/2017 Review 00