

CEMENT SCUD GEL

Sacrificial protective gel

DESCRIPTION

CEMENT SCUD GEL is a formulation designed to protect concrete surfaces. When applied on concrete surfaces, CEMENT SCUD GEL forms a film that prevents splashes of cement and/or lime from attacking the existing surface.

APPLICATION

- Paving stone washing
- Printed concrete
- Pavements
- Industrial flooring
- Printed walls
- Protection of stone and marble.

CEMENT SCUD GEL is particularly useful for the protection of perimeter walls and areas of marble or stone that lay adjacent to fresh concrete.

CEMENT SCUD GEL is removed by washing the surface with a pressure washer (the sketches will be removed along with the film).

CEMENT SCUD GEL is a product for PROFESSIONAL USE ONLY.

CONSUMPTION

The consumption per square metre depends on the porosity and type of surface to be treated.

Working temperature: 5-35°C

The product can be applied by:

- Brushing: pure.
- Spraying: diluted with up to 10% water, added slowly.

PACKAGE

14 kg plastic buckets.

Store in a dry place. SENSITIVE TO COLD.

The product, if properly stored, will last for 12 months.

WARNINGS

Always do a test on a hidden area before proceeding to apply to any surface.

After use, always close the container to prevent desiccation.

IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the intended use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed at any time. Ideal Work products are for professional use and the company organises periodical training for its customers on demand. Anyone who uses these products without qualification takes all the associated risks.

CERTIFIED ISO9002 - IST 0498 EDIT. 01 of 01 February 2001 Review 01 dtd 22/05/2015