

## IDEAL ACRYLIC

### Water based acrylic sealer for Ideal wall and Ideal Tix

#### DESCRIPTION

Ideal acrylic is a ready to use water based acrylic copolymer designed to protect and fix the colours on Ideal Wall or Ideal Tix. The acrylic copolymers provide a long lasting durable protective coating. Due to the medium solids it is a breathable hard wearing coating.

#### FEATURES

- Excellent water resistance
- Interior use only
- Increased life and resistance to abrasion
- Medium Solids
- Easy-to-Apply
- High Coverage Rates
- Can be sprayed

#### APPLICATION

Ideal acrylic can be spray applied to Ideal Wall or Ideal Tix in one or two applications. Apply at temperatures between +5 °C and +35 °C and at a relative humidity lower than 85%.

Allow 72 hours for the Ideal Acrylic to be completely cured

#### LIMITATION

**Ideal Acrylic is recommended for internal use.** For external use, we suggest to apply Ideal sealer regular.

#### COVERAGE

The average coverage is approximately 0.25 lt/m<sup>2</sup>. IDEAL ACRYLIC is a ready-to-use product which must not be diluted.

#### COLOUR

Ideal acrylic is milky white but will dry clear.

#### PACKAGING AND STORAGE

Ideal acrylic is packaged in 10 and 25 L containers

Ideal acrylic should be kept in a safe place and the seal should not be broken until use. Shelf life is approximately 1 year.

#### SENSITIVE TO FROST

##### IMPORTANT:

All the information contained in this sheet is based on the best practical and laboratory applications. It is the customer's responsibility to check the product is suitable for the use. The manufacturer declines any responsibility for wrong application. It is recommended to carry out tests on small areas before application. This sheet replaces and cancels any previous one. The data contained can be changed anytime. Ideal Work products are for professional use and the company organizes periodical training of its customers on demand. Anyone who uses these products without qualification, takes all the risks connected.

CERTIFIED ISO9002 - IST 0485 EDIT. 01 of 01 February 2001 Review 01 dtd 22/05/2015